
Server, 12
Server process, 12'
H2
13b
Data consuming
Application, 16d
H4
13c
H3
13a
Network, 18
Client, 14
Client process, 14'
H1
Data consuming
Application, 16a
10

FIG. 1


App. 16a
App 16d
H4
OI, 30d
AP, 28d
Chain, 32
18
20
H1
EP, 26a
OI, 30a
EI, 24a
AP, 28a
Chains, 32
H3
EP, 26c
AP, 28c
EI, 24c
s1
s2
s3
H2
EP, 26b
AP, 28b
EI, 24b

FIG. 2

FIG. 3


57, RM REC
LDM
Node Mgr, 52
RDM
node
node
H2
Admin Server, 12'
Admin Client, 14'
54
56
58
12
50
14
RDM
Node Mgr, 52
H1
node
node
LDM
58
57, RM REC
Fault Manager, 59
Recovery Manager, 61

FIG. 4


/ /input/24b
/26b
/28b
/28d
The input queues are where nodes look for files to process
/ /output/24b
/26b
/28b
The output queues are where nodes write their post-processed files
/ /scratch/24b
/25b
/28b
The scratch queues is used by the node to persist data
80


82, MASTER DATA FLOW MAP
Node
Destination
Queue
84a, NODE DATA FLOW MAP
Node
Destination
Queue
84i, NODE DATA FLOW MAP

FIG. 5


Launching other functional nodes, 132a
Provide nodes with configuration, 132b
Provide RMI registry 132c
Administer nodes maintain status of nodes, 132d

FIG. 6

FIG. 7


Data source, 91
Host H1
Local DFM
Node 92
Output 92b
LDM 93
Input 94a
Node 94
Output 94b
Remote DFM
RDM 99
Input 97a
Host H2
RDM 100
Input 102a
Node 102
Output 102b
90


Data Mgr.
93'
in
Node process, 58'
Out 92'
Out 92"
93"
96', queue
Node, 58
Persistent Store, 95

FIG. 8


SCAN NODE OUTPUT QUEUES, 112
FILES TO TRANSFER?, 114
yes
DETERMINE DESTINATIONS BASED ON DF MAP, 116
LOCAL DF MAP
COPY FILES TO DEST. NODE INPUT QUEUE, 118
TRANSFER COMPLETE?, 120
yes
REMOVE FILES FROM OUTPUT QUEUE OF SOURCE NODE, 122

FIG. 9



FIG. 10

Express Mail Label No. EV 339 920 125 US


Processor 320
310
325, Bus
RAM 321
Program Memory 322
Hard Drive Controller 323
I/O Controller 324
326, I/O Bus
Hard Disk 330
I/O Interface 327

FIG. 11